



Transocean Gelclean

Code: 7003

Product description

A specially formulated acid gel designed to rejuvenate painted surfaces by removing rust stains and surface oxidation from them. It is ideal for removing salt and contamination in general prior to application of a new coat of paint. Transocean Gelclean will brighten and remove surface oxidation formed on non-ferrous material such as aluminium.

Physical properties.

Colour/Appearance	Clear
Volume Solids	25%
Specific gravity	1.1 gr/ml
VOC	58 gr/liter
Flashpoint	None

Application data

The product is designed for application by brush or damp cloth. Apply liberally. Wait for 15 minutes or longer if necessary and then wash off with copious amounts of fresh water. Allow to dry before primer or finish application.

Surface preparation.

Painted surfaces	Painted surfaces should be dampened prior to application of Transocean Gelclean for best results.
Non-ferrous materials	On non-ferrous materials it should be applied direct to the surface.

Worldwide availability

The product is part of the common Transocean product range but local availability is subject to confirmation. Although we strive to supply the same product through the world, slight modifications of the product in some cases may be necessary in order to comply with local conditions and/or national regulations. In such cases an alternative datasheet will be issued.

Health and safety

Observe the precautionary notices on the label of the container. A material safety data sheet is available upon request and national or local safety regulations should be followed. This product is intended for use by professional applicators.

As a general rule, avoid skin- and eye contact by wearing overalls, gloves, goggles, mask, etc. Spillage on the skin should immediately be removed by thorough washing with lukewarm water and soap or a suitable industrial cleaner. Eyes should be flushed with fresh water and medical attention sought immediately. Spraying should be carried out under well-ventilated conditions. Avoid inhalation of solvent vapours and paint mist by wearing an air mask.

This product contains flammable materials and should be kept away from sparks and open flames. Smoking in the area should not be permitted.

Disclaimer

The information in this data sheet is provided to the best of our knowledge. However, we have no control over either quality or condition of the substrate and other factors affecting the use and application of this product.

Therefore, we cannot accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising from the use of this product.

We reserve the right to change the product without notice.

Date of issue: 24 August 2023.